



# Technical Data

## Double-Sided Termination Tape

DIVISION: 033000, 072600

### 1.0 PRODUCT NAME

Barrier-Bac Double-Sided Termination Tape

### 2.0 SUPPLIER

Inteplast Group  
9 Peach Tree Hill Road  
Livingston, NJ 07039

Technical Assistance  
TEL: (877) 535-0555  
FAX: (800) 709-6002  
www.barrierbac.com

### 3.0 PRODUCT DESCRIPTION

Barrier-Bac Double-Sided Termination Tape (DSTT) is a 25 mil, Double-Sided adhesive tape made to bond Barrier-Bac vapor barrier membrane to concrete, masonry, gypsum board, metal, wood and other surfaces.

#### 3.1 COMPOSITION

Barrier-Bac Double-Sided Termination Tape is a high performance, pressure sensitive tape, made from a blend of synthetic resins, thermoplastics and rubber.

#### 3.1 SIZE & PACKAGING

Barrier-Bac Double-Sided Termination Tape is available in standard size of 2" x 50' per roll.

16 rolls of Barrier-Bac Double-Sided Termination Tape are packed in a case. There are 48 cases per pallet.

Barrier-Bac Double-Sided Termination Tape weighs approximately 1.5 pounds per roll.

### 4.0 TECHNICAL DATA

Physical Properties of Barrier-Bac Double-Sided Termination Tape

Property	Test Method	Result
Peel Adhesion To Steel	ASTM D-1000	12 lbs/inch width
Elongation	ASTM D 882	700%
Dimensions	—	50 feet long 2 inches wide
Low Temperature Flexibility	ASTM C 765	Passes ½" radius@-34 degrees C, (-30 degrees F)
Water Vapor Test / Permeance	ASTM E 96 B	0.0112 perms
Application Temperature	—	40 degrees to 150 degrees F ambient
Service Temperature	—	-40 degrees F to 212 degrees F
VOC Content	—	None, 100% solids
Color	—	Gray

### 5.0 INSTALLATION

- All surfaces must be clean and dry.
- Attach tape on clean surface of vertical concrete or surface where Barrier-Bac vapor barrier membrane is to be terminated: next, remove release paper from tape then attach edge of Barrier-Bac vapor barrier membrane. Once Barrier-Bac vapor barrier membrane is properly placed, evenly seal vapor barrier to vertical concrete or other surface at termination point.
- Barrier-Bac Double-Sided Termination Tape (DSTT) is easily cut with scissors or utility knife.



## Technical Data

## Double-Sided Termination Tape

DIVISION: 033000, 072600

### 6.0 AVAILABILITY & COST

Barrier-Bac Double-Sided Termination Tape is available nationally through our network of building supply companies. Please contact our corporate office for a distributor in your area. Pricing may be obtained by contacting your local Barrier-Bac Products distributor or sales representative.

### 7.0 WARRANTY

We warrant and guarantee our specifications as published. Published test results are based upon accepted industry practices as well as the test methods called for and listed on our test documents. We believe, to the best of our knowledge, that our published results are accurate, reliable and represent our Double-Sided seam tape. Inteplast Group Ltd. cannot control site conditions and improper installation practices. Therefore, no warranty, expressed or implied, is given, including those of merchantability, fitness for a particular purpose or any other matter with respect to the product.

### 8.0 MAINTENANCE

No maintenance is required.

### 9.0 TECHNICAL SERVICES

Technical services for all of our products may be obtained by contacting our corporate office

Corporate Office:  
(877) 535-0555

### 10.0 FILING SYSTEMS

Barrier-Bac brochures are available from Barrier-Bac distributors, sales representatives, Inteplast Group, and our web site: [www.BarrierBac.com](http://www.BarrierBac.com)



**INTEPLAST GROUP**

OFFICE: 9 Peach Tree Hill Rd., Livingston, NJ 07039  
PLANT: 101 Inteplast Blvd., Lolita, TX 77971

TEL: 1-877-535-0555

FAX: 1-800-709-6002

E-MAIL: [info@BarrierBac.com](mailto:info@BarrierBac.com)

WEB SITE: [www.BarrierBac.com](http://www.BarrierBac.com)